

Package ‘hett’

October 13, 2022

Version 0.3-3

Date 2020-10-09

Title Heteroscedastic t-Regression

Author Julian Taylor <julian.taylor@adelaide.edu.au>

Maintainer Julian Taylor <julian.taylor@adelaide.edu.au>

Depends R (>= 2.0.0), MASS, lattice

Description Functions for the fitting and summarizing of heteroscedastic t-regression.

License GPL (>= 2)

NeedsCompilation no

Repository CRAN

Date/Publication 2020-10-13 10:50:02 UTC

R topics documented:

mm	1
rent	2
summary.tlm	3
tlm	4
tlm.control	7
tscore	8
tsum	9

Index	11
--------------	-----------

mm	<i>Excess returns for Martin Marietta company</i>
----	---

Description

Data from the Martin Marietta company collected over a period of 5 years on a monthly basis

Usage

```
data(mm)
```

Format

A data frame with 60 observations on the following 4 variables.

date the month the data was collected

am.can a numeric vector

m.marietta excess returns from the Martin Marietta company

CRSP an index for the excess rate returns for the New York stock exchange

Source

Bulter et al (1990). Robust and partly adaptive estimation of regression models. *Review of Economic Statistics*, **72**, 321-327.

Examples

```
data(mm, package = "hett")
attach(mm)
plot(CRSP, m.marietta)
lines(CRSP, fitted(lm(m.marietta ~ CRSP)), lty = 2)
```

rent

Rent for Land PLanted to Alfalfa

Description

Dataset collected in 1977 from Minnesota to study the variation in land rented for growing alfalfa

Usage

```
data(rent)
```

Format

A data frame with 67 observations on the following 5 variables.

Rent a numeric vector average rent per acre.

AllRent a numeric vector describing average rent paid for all tillable land.

Cows a numeric vector describing the density of dairy cows (number per square mile).

Pasture a numeric vector describing the proportion of farmland used as pasture.

Liming a factor with levels No if no liming is required to grow alfalfa and Yes if it does.

Source

Weisberg, S (1985). *Applied Linear Regression* Wiley: New York

Examples

```
library(lattice)
data(rent, package = "hett")
attach(rent)
xyplot(log(Rent/AllRent) ~ sqrt(Cows), groups = Liming, panel = panel.superpose)
```

summary.tlm	<i>summary method for class "tlm"</i>
-------------	---------------------------------------

Description

Summarizes the heteroscedastic t regression object

Usage

```
## S3 method for class 'tlm'
summary(object, correlation = FALSE, ...)
## S3 method for class 'summary.tlm'
print(x, ...)
```

Arguments

object	heteroscedastic t regression object called from <code>tlm()</code>
x	an object of class "summary.tlm" containing the values below
correlation	should the calculation of the parameter correlation matrix be suppressed. If the fit includes a location and a scale formula then both correlation matrices are printed. The default is FALSE.
...	arguments passed to or from other methods

Details

The table summary produced by this function should be used with caution. A more appropriate test between nested models is to use the score statistic function `tscore`.

Value

a list containing the following components:

loc.summary	an object containing a list of objects that summarize the location model
scale.summary	an object containing a list of objects that summarize the scale model

iter	the number of iterations of the algorithm
dof	value of the fixed or estimated degrees of freedom
dofse	the standard error associated with the degrees of freedom if estimated
logLik	the maximised log-likelihood
method	the method used to maximize the likelihood
endTime	the time taken for the algorithm to converge

Author(s)

Julian Taylor

See Also

[tsum](#), [t1m](#)

Examples

```
data(mm, package = "hett")
attach(mm)

## fit a model with heteroscedasticity and estimating the degrees of freedom

tfit2 <- t1m(m.marietta ~ CRSP, ~ CRSP, data = mm, start = list(dof =
3), estDof = TRUE)
summary(tfit2)
```

t1m

Maximum likelihood estimation for heteroscedastic t regression

Description

Fits a heteroscedastic t regression to given data for known and unknown degrees of freedom.

Usage

```
t1m(lform, sform = ~ 1, data = NULL, subset = NULL, contrasts =
NULL, na.action = na.fail, start = NULL, control = t1m.control(...),
obs = FALSE, estDof = FALSE, ... )

## S3 method for class 't1m'
print(x, ...)
```

Arguments

x	an object of class "t1m"
lform	a formula of the type response ~ terms, where terms can be of the form, for example, first + second or first*second(see lm for details)
sform	a formula of the type ~ terms, where terms can be of the form, for example, first + second or first*second(see lm for details).
data	the data in the form of a data.frame where the column names can be matched to the variable names supplied in lform and sform
subset	numerical vector to subset the data argument
contrasts	set of contrasts for the location model (see contrasts.arg for details)
na.action	the action to proceed with in the event of NA's in the response. Currently NA's are not allowed and therefore na.fail is the sole argument.
start	is a list of possibly four named components, ("beta", "lambda", "dof", "omega"), for the location, scale, degrees of freedom parameters and random scale effects respectively. Each component must be of the appropriate length.
control	is an argument to a function that maintains the control of the algorithm. The t1m.control()function contains the arguments, epsilon to determine how small the relative difference of likelihoods should be for convergence (default is 1e-07), maxit to determine the maximum iterations required (default = 50), trace if the user requires printing of estimates etc. as algorithm runs (default = FALSE), verboseLev to determine the amount of verbose printing to the screen as the algorithm runs (verboseLev = 1 displays location scale and dof estimates and the likelihood, verboseLev = 2 displays all of 1 plus the random scale effects)
obs	should the location parameters be calculated using the observed or expected information(default = FALSE). (Note: using the observed information does not calculate the appropriate standard errors, see DETAILS)
estDof	should the degrees of freedom parameter be estimated or not. If FALSE then the value given for dof in the start argument will be the fixed value used for the algorithm. If TRUE then the value given for dof in the start argument supplies an initial value only.
...	arguments passed to t1m.control() or to the print method

Details

When the degrees of freedom is unknown the code uses the non-linear optimiser nlm. If the response (and therefore the errors) is tending toward a Gaussian this optimisation will still converge but with very high degrees of freedom.

To obtain the appropriate standard errors from summary the user must specify the argument obs = F to ensure that the location parameter is calculated using the expected information.

Value

a list containing the following components:

loc.fit	an object containing the estimated location parameters and other elements associated with the location parameter model
scale.fit	an object containing the estimated scale parameters and other elements associated with the scale parameter model
random	the random scale effects
dof	fixed or estimated degrees of freedom
dofse	the standard error associated with the degrees of freedom
iter	the number of iterations of the algorithm
logLik	the maximised log-likelihood
endTime	the time taken for the algorithm to converge

Background

The theoretical background for this function can be found in Taylor and Verbyla (2004).

Author(s)

Julian Taylor

References

Taylor, J. D. & Verbyla, A. P (2004). Joint modelling of the location and scale parameters of the t -distribution. *Statistical Modelling* **4**, 91-112.

See Also

[summary.tlm](#)

Examples

```
data(mm, package = "hett")
attach(mm)

## fit a model with no heteroscedasticity and fixed degrees of freedom
tfit <- tlm(m.marietta ~ CRSP, data = mm, start = list(dof = 3))

## fit a model with heteroscedasticity and fixed degrees of freedom
tfit1 <- tlm(m.marietta ~ CRSP, ~ CRSP, data = mm, start = list(dof = 3))

## fit a model with heteroscedasticity and estimating the degrees of freedom
tfit2 <- tlm(m.marietta ~ CRSP, ~ CRSP, data = mm,
start = list(dof = 3), estDof = TRUE)
```

`t1m.control`*Auxiliary for Controlling t1m Fitting*

Description

Auxiliary function for fitting t1m model. Generally only used when calling t1m

Usage

```
t1m.control(epsilon = 1e-07, maxit = 50, trace = FALSE, verboseLev = 1)
```

Arguments

epsilon	positive convergence tolerance value. The iterations converge when $[\text{newlik} - \text{oldlik}] < \text{epsilon}/2$
maxit	integer giving the maximum iterations allowable for the routine
trace	logical. If TRUE output is printed to the screen during each iteration
verboseLev	integer. If 1 then print according to trace. If 2 then print random scale effects also.

Value

A list with the argument as values

Author(s)

Julian Taylor

See Also

[t1m](#)

Examples

```
data(mm, package = "hett")
attach(mm)

## change the maximum amount of iterations for the algorithm

fit1 <- t1m(m.marietta ~ CRSP, ~ 1, data = mm, start = list(dof = 3),
estDof = TRUE, control = t1m.control(maxit = 100))
```

tscore	<i>Score test for heteroscedastic t models</i>
--------	--

Description

Provides a score test for the location and scale parameters of the heteroscedastic t regression model.

Usage

```
tscore(..., data = NULL, scale = FALSE)
```

Arguments

...	Any number of arguments containing nested model fits from <code>tlm()</code> (see Details)
data	the data used to fit the models involved
scale	logical. If TRUE the scale model is tested

Details

The user must supply nested models that test, *either*, the scale or the location component of the model. The model objects *must* be nested from left to right. Currently there are no traps if the arguments are not given in this order.

The models must also have either, all fixed degrees of freedom or estimated degrees of freedom.

Value

Output containing the hypothesis, the score statistic, degrees of freedom for the test and the p-value are printed to the screen.

Author(s)

Julian Taylor

References

Taylor, J. D. & Verbyla, A. P (2004). Joint modelling of the location and scale parameters of the *t*-distribution. *Statistical Modelling* **4**, 91-112.

See Also

[tlm](#)

Examples

```
data(mm, package = "hett")
attach(mm)
tfit1 <- tlm(m.marietta ~ CRSP, ~ 1, data = mm, start = list(dof = 3),
  estDof = TRUE)

tfit2 <- tlm(m.marietta ~ CRSP, ~ CRSP, data = mm, start = list(dof =
  3), estDof = TRUE)

tscore(tfit1, tfit2, data = mm, scale = TRUE)
```

tsum	<i>Summary function for the scale or location component of a heteroscedastic t model</i>
------	--

Description

Summarizes the location *or* scale components of a heteroscedastic *t* model

Usage

```
tsum(object, dispersion = NULL, correlation = FALSE,
  symbolic.cor = FALSE, ...)

## S3 method for class 'tsum'
print(x, digits = max(3, getOption("digits") - 3), symbolic.cor =
  x$symbolic.cor, signif.stars = getOption("show.signif.stars"),
  scale = TRUE, ...)
```

Arguments

object	either the location <i>or</i> scale object created by fitting a heteroscedastic <i>t</i> object with <code>tlm</code>
x	an object of class "tsum"
dispersion	1 if summarizing the location model; 2 if summarizing the scale model (see Details)
correlation	logical; if TRUE, the correlation matrix of the estimated parameters is returned and printed.
digits	the number of significant digits to be printed.
symbolic.cor	logical. If TRUE, print the correlations in a symbolic form (see 'symnum') rather than as numbers.
signif.stars	logical. if TRUE, "significance stars" are printed for each coefficient.
scale	logical. If TRUE then the dispersion is known in advance (2), and is printed accordingly.
...	further arguments passed to or from other methods.

Details

The argument supplied to `dispersion` must be either 1 (location model) or 2 (scale model). The reason for this is because the fitting of the model has already scaled the covariance matrix for the location coefficients. Hence the scaled and unscaled versions of covariance matrix for the location model are identical.

This function will not be generally called by the user as it will only summarize the location or scale model but not both. Instead the user should refer to `summary.tlm` to print a summary of both models.

Value

`tsum` returns an object of class "tsum", a list with components

<code>call</code>	the component from object
<code>df.residual</code>	the component from object
<code>coefficients</code>	the matrix of coefficients, standard errors, z-values and p-values
<code>dispersion</code>	the supplied dispersion argument
<code>df</code>	a 2-vector of the rank of the model and the number of residual degrees of freedom
<code>cov.unscaled</code>	the unscaled (<code>dispersion = 1</code>) estimated covariance matrix of the estimated coefficients
<code>cov.scaled</code>	ditto, scaled by <code>dispersion</code>
<code>correlation</code>	(only if <code>correlation</code> is true.) The estimated correlations of the estimated coefficients
<code>symbolic.cor</code>	(only if <code>correlation</code> is true.) The value of the argument <code>symbolic.cor</code>

Author(s)

Julian Taylor

See Also

[summary.tlm](#), [tlm](#)

Examples

```
data(mm, package = "hett")
attach(mm)
tfit <- tlm(m.marietta ~ CRSP, ~ CRSP, data = mm, start = list(dof = 3),
estDof = TRUE)
tsum(tfit$loc.fit, dispersion = 1)
```

Index

* datasets

mm, 1
rent, 2

* distribution

summary.tlm, 3
tlm, 4
tlm.control, 7
tscore, 8
tsum, 9

* regression

summary.tlm, 3
tlm, 4
tlm.control, 7
tscore, 8
tsum, 9

mm, 1

print.summary.tlm(summary.tlm), 3
print.tlm(tlm), 4
print.tsum(tsum), 9

rent, 2

summary.tlm, 3, 6, 10

tlm, 4, 4, 7, 8, 10
tlm.control, 7
tscore, 8
tsum, 4, 9