

Package ‘wordvector’

March 12, 2025

Type Package

Title Word and Document Vector Models

Version 0.3.0

Maintainer Kohei Watanabe <watanabe.kohei@gmail.com>

Description Create dense vector representation of words and documents using 'quanteda'. Currently implements Word2vec (Mikolov et al., 2013) <[doi:10.48550/arXiv.1310.4546](https://doi.org/10.48550/arXiv.1310.4546)> and Latent Semantic Analysis (Deerwester et al., 1990) <[doi:10.1002/\(SICI\)1097-4571\(199009\)41:6%3C391::AID-ASI1%3E3.0.CO;2-9](https://doi.org/10.1002/(SICI)1097-4571(199009)41:6%3C391::AID-ASI1%3E3.0.CO;2-9)>.

URL <https://github.com/koheiw/wordvector>

License Apache License (>= 2.0)

Encoding UTF-8

RoxxygenNote 7.3.2

Depends R (>= 3.5.0)

Imports quanteda (>= 4.1.0), methods, stringi, Matrix, proxyC, RSpectra, irlba, rsvd

Suggests testthat, word2vec, spelling

LinkingTo Rcpp, quanteda

Language en-US

LazyData true

NeedsCompilation yes

Author Kohei Watanabe [aut, cre, cph] (<<https://orcid.org/0000-0001-6519-5265>>), Jan Wijffels [aut] (Original R code), BNOSAC [cph] (Original R code), Max Fomichev [ctb, cph] (Original C++ code)

Repository CRAN

Date/Publication 2025-03-12 11:20:02 UTC

Contents

<code>analogy</code>	2
<code>as.matrix.textmodel_wordvector</code>	3
<code>data_corpus_news2014</code>	3
<code>probability</code>	4
<code>similarity</code>	4
<code>textmodel_doc2vec</code>	5
<code>textmodel_lsa</code>	6
<code>textmodel_word2vec</code>	7
<code>weights</code>	9

Index	10
--------------	-----------

<code>analogy</code>	<i>Convert formula to named character vector</i>
----------------------	--

Description

Convert a formula to a named character vector in analogy tasks.

Usage

```
analogy(formula)
```

Arguments

<code>formula</code>	a formula object that defines the relationship between words using + or - operators.
----------------------	--

Value

a named character vector to be passed to [similarity\(\)](#).

See Also

[similarity\(\)](#)

Examples

```
analogy(~ berlin - germany + france)
analogy(~ quick - quickly + slowly)
```

```
as.matrix.textmodel_wordvector  
Extract word vectors
```

Description

Extract word vectors from a `textmodel_wordvector` or `textmodel_docvector` object.

Usage

```
## S3 method for class 'textmodel_wordvector'  
as.matrix(x, ...)
```

Arguments

x	a <code>textmodel_wordvector</code> or <code>textmodel_docvector</code> object.
...	not used

Value

a matrix that contain the word vectors in rows

```
data_corpus_news2014    Yahoo News summaries from 2014
```

Description

A corpus object containing 2,000 news summaries collected from Yahoo News via RSS feeds in 2014. The title and description of the summaries are concatenated.

Usage

```
data_corpus_news2014
```

Format

An object of class `corpus` (inherits from `character`) of length 20000.

Source

<https://www.yahoo.com/news/>

References

Watanabe, K. (2018). Newsmap: A semi-supervised approach to geographical news classification. *Digital Journalism*, 6(3), 294–309. <https://doi.org/10.1080/21670811.2017.1293487>

probability	<i>Compute probability of words</i>
--------------------	-------------------------------------

Description

Compute the probability of words given other words.

Usage

```
probability(x, words, mode = c("words", "values"))
```

Arguments

- x a textmodel_wordvector object fitted with normalize = FALSE.
- words words for which probability is computed.
- mode specify the type of resulting object.

Value

a matrix of probability scores when mode = "values" or of words sorted in descending order by the probability scores when mode = "words". When words is a named numeric vector, probability scores are weighted by the values.

See Also

[similarity\(\)](#)

similarity	<i>Compute similarity between word vectors</i>
-------------------	--

Description

Compute the cosine similarity between word vectors for selected words.

Usage

```
similarity(x, words, mode = c("words", "values"))
```

Arguments

- x a textmodel_wordvector object.
- words words for which similarity is computed.
- mode specify the type of resulting object.

Value

a matrix of cosine similarity scores when mode = "values" or of words sorted in descending order by the similarity scores when mode = "words". When words is a named numeric vector, word vectors are weighted and summed before computing similarity scores.

See Also

[probability\(\)](#)

textmodel_doc2vec *Create distributed representation of documents*

Description

Create distributed representation of documents as weighted word vectors.

Usage

```
textmodel_doc2vec(x, model, group_data = FALSE)
```

Arguments

- | | |
|------------|---|
| x | a quanteda::tokens object. |
| model | a textmodel_wordvector object. |
| group_data | if TRUE, apply dfm_group(x) before creating document vectors. |

Value

Returns a [textmodel_docvector](#) object with the following elements:

- | | |
|--------------|---|
| values | a matrix for document vectors. |
| dim | the size of the document vectors. |
| concatenator | the concatenator in x. |
| docvars | document variables copied from x. |
| call | the command used to execute the function. |
| version | the version of the wordvector package. |

textmodel_lsa	<i>Latent Semantic Analysis model</i>
---------------	---------------------------------------

Description

Train a Latent Semantic Analysis model (Deerwester et al., 1990) on a [quanteda::tokens](#) object.

Usage

```
textmodel_lsa(
  x,
  dim = 50,
  min_count = 5L,
  engine = c("RSpectra", "irlba", "rsvd"),
  weight = "count",
  verbose = FALSE,
  ...
)
```

Arguments

<code>x</code>	a quanteda::tokens object.
<code>dim</code>	the size of the word vectors.
<code>min_count</code>	the minimum frequency of the words. Words less frequent than this in <code>x</code> are removed before training.
<code>engine</code>	select the engine perform SVD to generate word vectors.
<code>weight</code>	weighting scheme passed to quanteda::dfm_weight() .
<code>verbose</code>	if TRUE, print the progress of training.
<code>...</code>	additional arguments.

Value

Returns a `textmodel_wordvector` object with the following elements:

<code>values</code>	a matrix for word vectors values.
<code>weights</code>	a matrix for word vectors weights.
<code>frequency</code>	the frequency of words in <code>x</code> .
<code>engine</code>	the SVD engine used.
<code>weight</code>	weighting scheme.
<code>concatenator</code>	the concatenator in <code>x</code> .
<code>call</code>	the command used to execute the function.
<code>version</code>	the version of the <code>wordvector</code> package.

References

Deerwester, S. C., Dumais, S. T., Landauer, T. K., Furnas, G. W., & Harshman, R. A. (1990). Indexing by latent semantic analysis. *JASIS*, 41(6), 391–407.

Examples

```
library(quanteda)
library(wordvector)

# pre-processing
corp <- corpus_reshape(data_corpus_news2014)
toks <- tokens(corp, remove_punct = TRUE, remove_symbols = TRUE) %>%
  tokens_remove(stopwords("en", "marimo"), padding = TRUE) %>%
  tokens_select("^[a-zA-Z-]+$", valuetype = "regex", case_insensitive = FALSE,
                padding = TRUE) %>%
  tokens_tolower()

# train LSA
lsa <- textmodel_lsa(toks, dim = 50, min_count = 5, verbose = TRUE)

# find similar words
head(similarity(lsa, c("berlin", "germany", "france"), mode = "words"))
head(similarity(lsa, c("berlin" = 1, "germany" = -1, "france" = 1), mode = "values"))
head(similarity(lsa, analogy(~ berlin - germany + france)))
```

textmodel_word2vec *Word2vec model*

Description

Train a Word2vec model (Mikolov et al., 2023) in different architectures on a [quanteda::tokens](#) object.

Usage

```
textmodel_word2vec(
  x,
  dim = 50,
  type = c("cbow", "skip-gram"),
  min_count = 5L,
  window = ifelse(type == "cbow", 5L, 10L),
  iter = 10L,
  alpha = 0.05,
  use_ns = TRUE,
  ns_size = 5L,
  sample = 0.001,
  normalize = TRUE,
```

```
verbose = FALSE,
...
)
```

Arguments

x	a <code>quanteda::tokens</code> object.
dim	the size of the word vectors.
type	the architecture of the model; either "cbow" (continuous back of words) or "skip-gram".
min_count	the minimum frequency of the words. Words less frequent than this in x are removed before training.
window	the size of the word window. Words within this window are considered to be the context of a target word.
iter	the number of iterations in model training.
alpha	the initial learning rate.
use_ns	if TRUE, negative sampling is used. Otherwise, hierarchical softmax is used.
ns_size	the size of negative samples. Only used when use_ns = TRUE.
sample	the rate of sampling of words based on their frequency. Sampling is disabled when sample = 1.0
normalize	if TRUE, normalize the vectors in values and weights.
verbose	if TRUE, print the progress of training.
...	additional arguments.

Details

User can changed the number of processors used for the parallel computing via `options(wordvector_threads)`.

Value

Returns a `textmodel_wordvector` object with the following elements:

values	a matrix for word vector values.
weights	a matrix for word vector weights.
dim	the size of the word vectors.
type	the architecture of the model.
frequency	the frequency of words in x.
window	the size of the word window.
iter	the number of iterations in model training.
alpha	the initial learning rate.
use_ns	the use of negative sampling.
ns_size	the size of negative samples.
concatenator	the concatenator in x.
call	the command used to execute the function.
version	the version of the wordvector package.

References

Mikolov, T., Sutskever, I., Chen, K., Corrado, G., & Dean, J. (2013). Distributed Representations of Words and Phrases and their Compositionality. <https://arxiv.org/abs/1310.4546>.

Examples

```
library(quanteda)
library(wordvector)

# pre-processing
corp <- data_corpus_news2014
toks <- tokens(corp, remove_punct = TRUE, remove_symbols = TRUE) %>%
  tokens_remove(stopwords("en", "marimo"), padding = TRUE) %>%
  tokens_select("^([a-zA-Z]+)$", valuetype = "regex", case_insensitive = FALSE,
                padding = TRUE) %>%
  tokens_tolower()

# train word2vec
w2v <- textmodel_word2vec(toks, dim = 50, type = "cbow", min_count = 5, sample = 0.001)

# find similar words
head(similarity(w2v, c("berlin", "germany", "france"), mode = "words"))
head(similarity(w2v, c("berlin" = 1, "germany" = -1, "france" = 1), mode = "values"))
head(similarity(w2v, analogy(~ berlin - germany + france), mode = "words"))
```

weights

[experimental] Extract word vector weights

Description

[experimental] Extract word vector weights

Usage

```
weights(x, mode = c("words", "values"))
```

Arguments

- | | |
|------|---|
| x | a <code>textmodel_wordvector</code> object. |
| mode | specify the type of resulting object. |

Value

a matrix of word vector weights when `mode = "value"` or of words sorted in descending order by the weights when `mode = "word"`.

Index

* **datasets**
 data_corpus_news2014, 3

analogy, 2
as.matrix.textmodel_wordvector, 3

data_corpus_news2014, 3

formula, 2

probability, 4
probability(), 5

quanteda::dfm_weight(), 6
quanteda::tokens, 5–8

similarity, 4
similarity(), 2, 4

textmodel_doc2vec, 5
textmodel_lsa, 6
textmodel_word2vec, 7

weights, 9